



WIFI Local Blink Server based 8 Relays ON/OFF

DINESH KUMAR

ISRO SATELLITE CENTER, BANGALORE

```
// OUTDOOR
#define BLYNK_PRINT Serial
#include <ESP8266WiFi.h>
#include <BlynkSimpleEsp8266.h>
char auth[] = "KWRfGs4ZLjqNxV5ZQf0OVR8h_ltnL75A";
char ssid[] = "Xiaomi_A5A0";
char pass[] = "pwd";
void setup()
{
  Serial.begin(115200);
  pinMode(D0,OUTPUT);
  pinMode(D1,OUTPUT);
  pinMode(D2,OUTPUT);
  pinMode(D3,OUTPUT);
  pinMode(D4,OUTPUT);
  pinMode(D5,OUTPUT);
  pinMode(D6,OUTPUT);
  pinMode(D7,OUTPUT);
  pinMode(D8,OUTPUT);
  digitalWrite(D0,HIGH);
  digitalWrite(D1,HIGH);
  digitalWrite(D2,HIGH);
  digitalWrite(D3,HIGH);
  digitalWrite(D4,HIGH);
  digitalWrite(D5,HIGH);
  digitalWrite(D6,HIGH);
  digitalWrite(D7,HIGH);
  digitalWrite(D8,HIGH);
  Blynk.begin(auth, ssid, pass, IPAddress(192,168,0,188), 8080);
}
void loop()
{ Blynk.run();}
```